

TW 500

S | Ø24 mm
Ø30 mm

TWS 500

PREMIUM



SOLID SHAFT Ø 24 mm / Ø 30 mm › ALBERO MASCHIO Ø 24 mm / Ø 30 mm › EJE MACHO Ø 24 mm / Ø 30 mm

Code Codice Codigo	Model Modello Modelo	Version										
			mm	rpm	l/min US gpm	bar	psi	Mpa	HP	kW	kg	lb
6513 2800	TW 3070	S	24	1450	10,5 2,8	503	7300	50,3	13,3	9,9	23,0	50,7
6513 2000	TW 3570	S	24	1450	13,0 3,4	503	7300	50,3	16,5	12,1	23,0	50,7
6513 1801	TW 4070	S	24	1450	14,8 3,9	503	7300	50,3	18,8	13,8	23,0	50,7
6513 1800	TW 4070	S	30	1450	15,2 4,0	503	7300	50,3	19,3	14,2	23,0	50,7
6513 2100	TW 4570	S	30	1450	16,2 4,3	503	7300	50,3	20,2	14,9	23,0	50,7
6513 1900	TW 5070	S	30	1450	19,9 5,3	503	7300	50,3	25,2	18,6	23,0	50,7
6513 1500	TW 5570	S	30	1450	22,0 5,8	503	7300	50,3	27,9	20,5	23,0	50,7
6514 1200	TWS 4070	S	24	1750	15,7 4,1	503	7300	50,3	19,3	14,6	23,0	50,7
6514 1300	TWS 4570	S	30	1750	17,5 4,6	503	7300	50,3	22,1	16,3	23,0	50,7
6514 1400	TWS 5070	S	30	1750	18,4 4,9	503	7300	50,3	23,2	17,1	23,0	50,7
6514 1500	TWS 6070	S	30	1750	22,5 6,0	503	7300	50,3	28,5	21,0	23,0	50,7
6514 1600	TWS 7070	S	30	1750	26,7 7,0	503	7300	50,3	33,7	24,7	23,0	50,7

