



PTO



- 1** Coupling to the tractor's 3rd point diam. 19 - 25 mm
Attacco al terzo punto trattore diam. 19 - 25 mm
Enganche al tercer punto del tractor Ø 19 - 25 mm
- 2** 22 mm diam. linkage pins for 3-point hitch
Perni diametro 22 mm per attacco ai bracci del sollevatore
Pernos de diámetro 22 mm para enganche a los brazos del elevador
- 3** Gearbox kit for 1450 rpm pumps (RW)
Moltiplicatore per pompe a 1450 giri/min (RW)
Multiplicador para bombas de 1450 rpm (RW)



STANDARD ACCESSORIES › DOTAZIONE STANDARD › DOTACIÓN ESTÁNDAR

	GH 351 gun with Swivel, n. 2 o-ring Pistola GH 351 con swivel, n. 2 o-ring Pistola GH 351 con swivel, n. 2 o-ring		Bent double barrel lance, without nozzles Lancia a canna doppia angolata, senza ugelli Lanza de doble caña, sin boquillas
	Detergent nozzle 1/4" MEG connection Ugello detergente attacco 1/4" MEG Boquilla detergente conexión 1/4" MEG		Fan shape nozzle 25°, 1/4" MEG connection Ugello con getto a lama 25° attacco 1/4" MEG Boquilla con chorro plano 25° conexión 1/4" MEG
	SAE 100, 10 m rubber delivery hose kit Kit tubo gomma mandata SAE 100 - 10 m Kit tubo de manguera SAE 100 - 10 m		Water suction filter Filtro aspirazione acqua Filtro de aspiración de agua

Code Codice Codigo	Model Modello Modelo	Frame Telaio Bastidor						Reduction gear-box Moltiplic. di giri Multipli. de rev				
			rpm	l/min		US gpm	bar			psi	Mpa	HP
9045 0014	RW 5530 21/200	✓	550	21,0	5,5	200	2900	20,0	10,4	7,7	✓	57x82,5x70
9045 0003	TWN 6036 23/200	✓	1000	23,0	6,0	200	2900	20,0	11,4	8,4		57x82,5x70
9045 0005	TWN 8025 30/170	✓	1000	30,0	7,9	170	2465	17,0	12,8	9,4		57x82,5x70
9045 0017	RW 4022 15/150		550	15,0	4,0	150	2175	15,0	5,9	4,4	✓	57x82,5x70
9045 0016	RW 5530 21/200		550	21,0	5,5	200	2900	20,0	10,4	7,7	✓	57x82,5x70
9045 0008	TWN 6036 23/200		1000	23,0	6,0	200	2900	20,0	11,4	8,4		57x82,5x70
9045 0010	TWN 8025 30/170		1000	30,0	7,9	170	2465	17,0	12,8	9,4		57x82,5x70